

# Contop® Plus



## A PREMIXED NON METALLIC FLOOR HARDENER

### DESCRIPTION

Contop Plus is a premixed non metallic floor hardener used to form monolithically hardened concrete floors. Contop Plus provides a hardened abrasion resistant surface and can also be used to inhibit dust formation.

### USES & ADVANTAGES

Used to provide a low cost, heavy duty concrete floor subject to heavy loads and traffic e.g. workshops, warehouses, car parks, garages, production areas, hospitals, schools, commercial floors, shopping centres, loading bays, industrial complexes etc.

#### Advantages include:-

- High abrasion resistance.
- High impact resistance.
- Increases the strength of surface.
- Resistant to petrol, mineral solvents and common chemicals.
- Creates dense, easy to clean surfaces.
- Non dusting nor rusting.
- Suitable for wet areas.
- Available in a range of colours.

### PROPERTIES

**Appearance:** Grey, green, red, yellow or cream

**Specific Gravity:** 1.4 kg./L.

**Moh Hardness:** Aggregate 7-8 (steel score)

**Abrasion Resistance:** Concrete improved by at least 225%

Tested to ASTM D4060 Taber Abrader & BS 6431 Part 20

### METHOD OF USE / APPLICATION

Once the freshly poured and levelled concrete has reached its plastic state the substrate should be smoothened using mechanical trowels. After bleed water has evaporated and concrete has a wet shine. Contop Plus should be sprinkled over the concrete surface at the recommended rate of application.

When the applied Contop Plus appears uniformly moistened level out with a wood float or a power float. Finish with a steel trowel to obtain a smooth, uniform surface.

### CURING

Correct curing should be applied e.g. Corcure 90 to prevent rapid loss of water, crazing and bloom.

### SUBSEQUENT FINISHES

Due to its high density & low porosity subsequent finishes are not normally required. Congard Acrylic may be used as a further sealer, however, tests must be carried out first.

### IMPORTANT NOTES

In very aggressive conditions where very high abrasion or impact resistance is required consideration should be given to Contop Plus E or Contop Plus Metallic.

### COVERAGE RATES

3 - 5 kg. / m<sup>2</sup> for medium to heavy traffic.

### PACKAGING

25 kg. 4 Ply plastic lined bags.

### STORAGE & SHELF LIFE

Store in dry conditions in unopened bags.

The shelf life is 12 months if stored correctly.

### HEALTH & SAFETY

Contop Plus is alkaline avoid contact with skin & eyes. Gloves, goggles and a dust mask should be worn. Skin should be washed with water to remove & splashes in the eyes washed out with copious amounts of clean water and medical attention sought. Contop Plus is nonflammable.

### TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

### QUALITY ASSURANCE

ISO 9001 : 2008 verified by TUV Nord.

### CONTACT DETAILS

Cormix International Limited

Regional Office,

89 Romklao Rd., Sansab, Minburi, Bangkok 10510

Tel. (66 2) 917 3955-8, 543 8890

Fax. (66 2) 917 3959, 543 8891

<http://www.cormix.com> E-mail : [info@cormix.com](mailto:info@cormix.com)

NOTE : Every reasonable precaution is taken in the manufacture of all CORMIX-products to ensure that they comply with CORMIX's high standard of quality. The recommendations and properties of the product are based upon what is believed to be the most reliable information available, and are not intended as recommendations which infringe on other patents. Although all CORMIX-products are subject to rigid quality tests, no specific guarantee can be given, because results depend, not only on quality, but also on other factors beyond our control. We welcome therefore consultation in the event of doubt concerning application, or performance, and point out that oral recommendations, which vary from the instructions contained herein, are not binding without written confirmation by CORMIX. All transactions shall be subject to our terms and conditions of sale-delivery-and-service. This data sheet supersedes the previous one and a reprint may be issued without notice to supersede this edition, as and when deemed necessary. The information given in this leaflet is to the best of our knowledge true and reliable. Field service where provided does not constitute supervisory responsibility. Our guarantee is therefore limited to the quality of materials delivered.