

BITUMIX WOOD PRESERVATIVE CLEAR

TECHNICAL DATA SHEET

DESCRIPTION

BITUMIX WOOD PRESERVATIVE CLEAR Provides excellent protective coating on wood and timber which is highly resistant to all types of Termites , ants, common insects and other micro organism such as fungi.

PACKING

Available in 200 L Steel drums / 10 L Cans & 4 L Cans.

COMPOSITION

BITUMIX WOOD PRESERVATIVE CLEAR consists of an effective fungicide and insecticide in a penetrative hydro carbon solvent.

SURFACE PREPARATION

Ensure that the timber is dry and properly seasoned. Used sand paper to obtain even surface, if required.

APPLICATION

It is ready to use. Apply uniformly by brush or the object can be immersed in Bitumix wood preservative for one hour. Allow minimum overnight drying before application of protective coating such as varnish or enamel paint.

COVERAGE

Approximately 5 m²/L to 10 m²/L

SHELF LIFE

18 to 24 months, in undamaged, tightly sealed containers. Containers must be kept sealed and stored away from sources of heat and ignition.

Page 1 of 2



BITUMIX WOOD PRESERVATIVE CLEAR

CLEANING OF TOOLS

Tools may be cleaned with Mineral turpentine or Thinner

HEALTH AND SAFETY

Poisonous. Keep away from foodstuff and children. Use gloves, goggles and protective clothing when using the product. Do not smoke while handling. Avoid contact with skin or eyes. If contact with skin, wash with soap and water. If contact with eyes, flush with plenty of water and seek medical advice.